

AL750

ARTICULATED LOADER

GEHL®



KEY FEATURES

- 4-Post Canopy ROPS and FOPS Certified
- Cabin with Heat and Air Conditioning*
- Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- Inching Pedal
- Digital Display with Audible and Visual Indicators
- Differential Lock (Hydraulically Activated Front and Rear)
- Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- Lift Arm with Z-Bar Kinematics Return to Dig and Mechanical Self-Level
- Lift Arm Float Detent
- 3-Speed*
- Hydraglide™ Ride Control*
- High-Flow Auxiliary Hydraulics*

WWW.GEHL.COM



AL750 ARTICULATED LOADER

SPECIFICATIONS

		IMPERIAL	METRIC
DIMENSIONS	Height to Top of Cab / ROPS	8' 2"	2.48 m
	Width over Tires	5' 9"	1.74 m
	Length to Carriage	14' 7"	4.44 m
	Maximum Lifting Height (below forks)	10' 9"	3.28 m
	Maximum Dump Angle at Full Height	45°	
	Outer Turning Radius	11' 2"	3.4 m
	Articulation Angle from Center	45°	
CAPACITIES	Static Tipping Load with Bucket Straight	7,446 lbs	3378 kg
	Static Tipping Load with Bucket Full Turn	5,778 lbs	2621 kg
	Static Tipping Load with Forks Straight	6,043 lbs	2741 kg
	Static Tipping Load with Forks Full Turn	4,793 lbs	2174 kg
	Bucket Breakout	13,277 lbf	5906 daN
	Operating Weight with Bucket	10,919 lbs	4953 kg
ENGINE	Engine Manufacturer	Deutz	
	Model / Number of Cylinders	TCD 3.6 L4 / 4	
	Gross Power @ 2300 rpm	74.4 hp	55.4 kW
	Displacement	0.95 gal	3.6 L
HYDRAULICS	Work Hydraulic System Flow	18.5 gal/min	70 L/min
	Drive Hydraulic System Pressure	5511 psi	380 bar
	Drive Hydraulic Reservoir Capacity	19.55 gal	74 L
OTHER	Travel Speed	12.4 mph	20 kph
	Fuel Tank Capacity	27 gal	120 L
	Tires	405 / 70-20	

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517



STANDARD FEATURES

- 4-Post Canopy ROPS and FOPS Certified
- Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- Hydrostatic 2-Speed Transmission
- Load Arm Float Detent
- Inching Pedal
- Electronic Hand Throttle
- Digital Display with Audible and Visual Indicators
- Steering Column with Tilt and Extension Adjustments
- Cup Holder
- Differential Lock (Hydraulically Activated Front and Rear)
- Oscillating Front Frame
- Rubber Floor mat
- Power-A-Tach® Attachment Mounting System (EuroStyle, 4-Point & Skid Steer)
- Adjustable Arm Rest
- Seven-Way Adjustable Seat
- 12-Volt Socket in Arm Rest
- Lift Arm with Z-Bar Kinematics, Return to Dig and Mechanical Self-Level
- Multi-Function Joystick
- Lift / Tilt Electronic Lockout Switch
- Reverse and Brake Tail Lights
- Master Electrical Disconnect Switch
- Articulation Locking Bar (conforms to SAEJ276)
- Horn
- Side View Mirrors
- Front, Rear & Boom Worklights

OPTIONAL FEATURES

- 4-Post Canopy with Front and Rear Windows
- Cabin with Heat
- Cabin with Heat and Air Conditioning
- 3-Speed - 5 / 12 / 19 mph (8 / 20 / 30 km/hr)
- Seven-Way Adjustable Air Suspension Seat with or without Sewn Cushions
- LED Work Lights
- Speed Control
- Back-up Alarm
- Hydraglide™ Ride Control
- Rear Auxiliary Hydraulics
- Additional Set of Front Auxiliary Hydraulics
- High-Flow Auxiliary Hydraulics
- Radio (Bluetooth Hands-Free)
- Rotating Beacon
- Strobe Light
- Lockable Tool Box
- Engine Block Heater
- Front and Rear 12-Volt Electric Auxiliary
- License Plate Holder
- Electric Attachment Control 14-Pin Harness with Switches
- Rear Hitch - Clevis or Receiver
- 3 inch (75 mm) Seatbelt