

ALT750

TELESCOPIC ARTICULATED LOADER

GEHL®



KEY FEATURES

- 4-Post Canopy ROPS and FOPS Certified
- Cabin with Heat and Air Conditioning*
- Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- Inching Pedal
- Digital Display with Audible and Visual Indicators
- Differential Lock (Hydraulically Activated Front and Rear)
- Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- Telescopic Lift Arm with Z-Bar Bucket Linkage and Mechanical Self-Level
- Lift Arm Float Detent
- 3-Speed*
- Hydraglide™ Ride Control*
- High-Flow Auxiliary Hydraulics*

*Optional features

ALT750 TELESCOPIC ARTICULATED LOADER



SPECIFICATIONS

	IMPERIAL	METRIC	
DIMENSIONS	Height to Top of Cab / ROPS (mm)	8' 2"	2476 mm
	Width over Tires (mm)	6' 5"	1957 mm
	Length with Bucket on Ground (mm)	18' 10"	5730 mm
	Bucket Hinge Pin Height Retracted (mm)	12' 10"	3911 mm
	Bucket Hinge Pin Height Extended (mm)	16' 6"	5036 mm
	Maximum Dump Angle at Full Height	45°	
	Outer Turning Radius (mm)	13' 3"	4030 mm
	Articulation Angle from Center	40°	
CAPACITIES	Static Tipping Load with Bucket Retracted	7,714 lbs.	3499 kg
	Static Tipping Load with Bucket Extended	4,013 lbs.	1820 kg
	Bucket Breakout (kg)	10,052 lbs.	4990 kg
	Operating Weight with Bucket (kg)	12,300 lbs.	5579 kg
ENGINE	Engine Manufacturer	Deutz	
	Model / Number of Cylinders	TD 3.6 L / 4	
	Gross Power @ 2300 rpm (kW)	74 hp	55 kW
	Displacement (L)	220 cu. in.	3.6 L
HYDRAULICS	Work Hydraulic System Flow (L/min)	18.4 gpm	70 L/min
	Drive Hydraulic System Pressure (bar)	5,500 psi	380 bar
	Drive Hydraulic Reservoir Capacity (L)	19.5 gal.	73.7 L
OTHER	Travel Speeds (km/hr)	7/12 mph	8/20 km/hr
	Battery	12 V	
	Fuel Tank Capacity (L)	30 gal.	115 L
	Tires	405 / 70 20	

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

STANDARD FEATURES

- 4-Post Canopy ROPS and FOPS Certified
- Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- Hydrostatic 2-Speed Transmission
- Load Arm Float Detent
- Inching Pedal
- Electronic Hand Throttle
- Digital Display with Audible and Visual Indicators
- Steering Column with Tilt and Extension Adjustments
- Cup Holder
- Differential Lock (Hydraulically Activated Front and Rear)
- Oscillating Front Frame
- Rubber Floor mat
- Power-A-Tach® Attachment Mounting System (EuroStyle, 4-Point & Skid Steer)
- Adjustable Arm Rest
- Seven-Way Adjustable Seat
- 12-Volt Socket in Arm Rest
- Telescopic Lift Arm With Z-Bar Bucket Linkage & Mechanical Self-Level
- Multi-Function Joystick
- Lift / Tilt Electronic Lockout Switch
- Reverse and Brake Tail Lights
- Master Electrical Disconnect Switch
- Articulation Locking Bar (conforms to SAEJ276)
- Horn
- Side View Mirrors
- Front, Rear & Boom Worklights

OPTIONAL FEATURES

- 4-Post Canopy with Front and Rear Windows
- Cabin with Heat
- Cabin with Heat and Air Conditioning
- 3-Speed - 5 / 12 / 19 mph (8 / 20 / 30 km/hr)
- Seven-Way Adjustable Air Suspension Seat with or without Sewn Cushions
- LED Work Lights
- Speed Control
- Back-up Alarm
- Hydraglide™ Ride Control
- Rear Auxiliary Hydraulics
- Additional Set of Front Auxiliary Hydraulics
- High-Flow Auxiliary Hydraulics
- Radio (Bluetooth Hands-Free)
- Rotating Beacon
- Strobe Light
- Lockable Tool Box
- Engine Block Heater
- Front and Rear 12-Volt Electric Auxiliary
- License Plate Holder
- Electric Attachment Control 14-Pin Harness with Switches
- Rear Hitch - Clevis or Receiver
- 3 inch (75 mm) Seatbelt



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517