

# RT195 - NEW

## COMPACT LOADERS



### Key Features

- ✓ Multiple Track Widths and Tread Patterns
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Pilot Operated Joystick Controls
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-out Cooler

### Key Specifications

- ✓ 2,787 lbs. (1264 kg) Rated Operating Capacity (50%)
- ✓ 69.3 hp (51.7 kW) Yanmar Engine 4TNV98C-NMS2, Stage IV
- ✓ 120" (3048 mm) Height to Hinge Pin
- ✓ 69" (1749 mm) Overall Machine Width Less Bucket
- ✓ 78" (1979 mm) Overall Height to top of ROPS

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Operating Weight	8150 lb	3697 kg
	Unladen weight	7544 lb	3422 kg
	Operating Capacity at 35% Tipping Load	1950 lb	884.50 kg
	Operating Capacity At 50% Tipping Load	2787 lb	1264 kg
	Tipping capacity	5571 lb	2527 kg
Weight and dimensions	Overall Operating Height - Fully Raised	158 in	4018 mm
	Height to Hinge Pin - Fully Raised	120 in	3048 mm
	Dump reach - Full height	26 in	648 mm
	Dump angle at full height	39 °	39 °
	Overall length with bucket	129 in	3279 mm
	Departure angle	27 °	27 °
	Ground clearance	7 in	188 mm
	Overall width less bucket	69 in	1746 mm
	Bucket Width	70 in	1778 mm
	Clearance Radius - Front with Bucket	81 in	2063 mm
Engine	Engine brand	Yanmar	Yanmar
	Engine model	4TNV98C-NMS2V	4TNV98C-NMS2V
	Gross Power	51.70 kW	51.70 kW
	Max. torque / Engine rotation	178 ft/lbs @ 2500 rpm	241 Nm @ 2500 rpm
	Power	51 kW	51 kW
	Battery voltage	12 V	12 V
	Accessory plug	120 V	120 V
Transmission	Alternator - Ampere	100 A	100 A
	Transmission type	Hydrostatic	Hydrostatic
Hydraulics	Standard flow - Auxiliary hydraulics	19 US gpm	71 l/min
	Auxiliary Hydraulic Pressure	5511 PSI	380 bar
	High-Flow Auxiliary Hydraulics - Option	30 US gpm	113 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	6092 PSI	420 bar
Tank capacities	Hydraulic tank capacity	10 US gal	36 l
	Fuel tank	16 US gal	58.70 l
	Liquid cooling tank volume	3 US gal	12.90 l
	Displacement / Number of cylinders	0.87 US gal / 4	3.30 l / 4
Noise and vibration	Noise to environment (LwA)	101.40 dB	101.40 dB
	Noise at driving position (LpA)	82 dB	82 dB
	Whole-Body Vibration (ISO 2631-1)	1.10 m/s²	1.10 m/s²



STANDARD FEATURES

- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydraloc™ Safety System
- Brake Control (Auto / Manual)
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- Hydrostatic Drive - Servo
- 12Volt Power Port
- Horn
- Two-Speed Drive
- Cup Holder
- High-Back Adjustable Seat
- Integral Access Plate (removable)
- Pilot Joystick Controls
- Lift Arm Support Device
- All-Tach® Attachment Mounting System
- Operator Restraint Bar
- IdealTrax® automatic track tensioning system

OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action 4
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Cab Enclosure
- Suspension Seat - Mechanical
- Back-Up Alarm
- Engine Block Heater
- Cabin with Heat
- Hydraglide™ Ride Control
- Air Ride Suspension Seat
- High-Flow Auxiliary Hydraulics
- Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT