

V330 GEN:2

SKID LOADER



KEY FEATURES

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Vertical Style Lift Path
- ✓ 4 Cylinder Turbo Diesel Engine
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar, Hand/Foot or Joystick Control System
- ✓ Zero Maintenance Axles w/8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner

KEY SPECIFICATIONS

- ✓ Operating capacity (50%) – 1497 kg (3,300 lbs.)
- ✓ Overall height to top of ROPS – 2083 mm (82")
- ✓ Gross Power – 53.7 kW (72 hp) @ 2500 rpm
- ✓ Yanmar / 4TNV98C-NMSLV / Stage V
- ✓ 294.2 Nm (217 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3332 mm (131.2") height to hinge pin
- ✓ 1819 mm (71.6") machine width - less bucket
- ✓ 4123 kg (9,090 lbs.) operating weight

V330 GEN:2 SKID LOADER

SPECIFICATIONS

		IMPERIAL	METRIC
DIMENSIONS	Overall Operating Height - Fully Raised	172"	4369 mm
	Height to Hinge Pin - Fully Raised	131.2"	3332 mm
	Overall Height to Top of ROPS	82"	2083 mm
	Overall Length with Bucket (w/o Counterweight)	152.5"	3874 mm
	Dump Angle at Full Height	42°	
	Dump Height - Fully Raised	98.5"	2502 mm
	Dump Reach at Full Height	32"	813 mm
	Maximum Rollback Angle at Ground	29°	
	Rollback Angle at Full Height	94°	
	Seat to Ground Height	41"	1041 mm
	Wheelbase	49.5"	1257 mm
	Overall Width - Less Bucket ^A	71.6"	1819 mm
	Bucket Width	74"	1880 mm
	Ground Clearance to Chassis	9"	229 mm
	Overall Length without Bucket (w/o Counterweight)	119"	3023 mm
	Rear Departure Angle	25°	
	Clearance Radius - Front with Bucket	94.5"	2400 mm
	Clearance Radius - Front without Bucket	56"	1422 mm
	Clearance Radius - Rear (w/o Counterweight)	69.5"	1765 mm
	Standard Specification Tire Size	14.00x17.5 HD	
ENGINE	Make	Yanmar	
	Model	4TNV98C-NMSLV / Stage V	
	Gross Power @ 2500 rpm	72 hp	53.7 kW
	Net Power @ 2500 rpm	70.7 hp	52.7 kW
	Maximum Torque @ 1625 rpm	217 ft-lbs.	294.2 Nm
	Displacement	202.6 cu.in.	3.3 L
HYDRAULICS	Auxiliary Hydraulic Flow - Standard	23.5 gpm	89 L/min
	High-Flow Auxiliary Hydraulics - Option	35 gpm	132 L/min
	Reservoir Capacity	10.5 gal	40 L
ELECTRICAL	Battery	12-volt	950 CCA
	Starter	12-volt	3.0 kW
	Alternator	100-amp	
CAPACITIES / WEIGHTS	Rated Operating Capacity ^B	3,300 lbs.	1497 kg
	Rated Operating Capacity with Optional Counterweight ^B	N/A	
	Fuel Tank	24.5 gal.	92.7 L
	Travel Speed - Maximum	8.4 mph	13.5 km/hr
	Travel Speed with Two-Speed Option - Maximum	12.5 mph	20.1 km/hr
	Operating Weight ^C - Approximate	9,090 lbs.	4123 kg
SOUND / VIBRATION*	Noise Level / Environmental Level	101 dB	
	Operator Ear	85 dB	
	Hand / Arm Vibration	1.50 m/s ²	
	Whole Body Vibration	1.07 m/s ²	

* Standard seat option and T-Bar controls

A Overall width is dependent upon the amount of wheel offset

B Per SAE J8181, SAE J732, and ISO 14397

C Weight of base unit with standard equipment, standard tires (heavy-duty flotation), standard dirt-construction bucket and 175 lbs. (79 kg) operator.

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.



STANDARD FEATURES

- Vertical Style Lift Arms
- Control type: Dual T-Bar, Hand/Foot or Joystick
- 4 Cylinder, Turbo Engine
- Fuel Gauge with Real Time Fuel Consumption
- All-Tach™ Attachment System (Universal-Style)
- Warning Lamps and Buzzer – Engine and Hydraulic Oil Temperature
- Battery Charge Indicator Lamp
- Low Oil Pressure Light and Buzzer
- Seatbelt Indicator Lamp and Buzzer
- Coolant Temperature Gauge
- Hourmeter
- Manual-Control Hydrostatic Drive
- ROPS/FOPS- Level II – Approved Overhead Guard
- Operator Restraint Bar with Armrests
- Independent Hydraulic Reservoir and Hydraulic Oil Cooler
- Engine Intake Air Pre-Heater Starting Assist
- Adjustable Seatbelt
- Lift Arm Support Device
- Hydraloc™ System
- Dual Front and Rear Work Lights
- Dual, Integral Cleanout Plates
- Vandalism Lock Provisions - Fuel and Engine Cover
- Acoustical Sound Material and Deluxe Headliner
- Deluxe High Back, Cushion Seat
- Front Auxiliary Hydraulics with 3/4-inch Flat-Faced Couplers
- Visual Hydraulic Filter Indicator
- Power Plug (12 V)
- Horn

OPTIONAL FEATURES

- Hydraglide™ Ride Control System
- Power-A-Tach® - Hydraulic Powered Attach System
- Switchable Self-Leveling Hydraulic Lift Action
- Engine Block Heater
- Suspension Seat
- Cab Door with Wiper
- Sliding Side Windows
- Sub-Zero Crankcase Kit
- Heater/Defroster
- Bluetooth Radio & Speakers
- 3-inch Wide Seatbelt – When Required by Law
- Audible Back-Up Alarm
- Rear View Mirror
- Rear Camera - Includes 5" (127 mm) Display
- Engine Auto-Shutdown System
- Interior Dome Light
- Centrifugal Pre-Cleaner
- Rotating Beacon
- Impact-Resistant Door
- Lift Kit - Single Point Lift System
- Bucket Bolt-On Cutting Edge
- Easy Manager Telematics
- Battery Disconnect Switch
- Work Light Kit (LED)



gehl.com

One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT