

VT210

TRACK LOADER

GEHL®



KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- IdealTrax™ Auto Tensioning System
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Dual Flange Idlers - Front + Rear
- **NOW STANDARD** Pilot Joystick Controls
- **NOW STANDARD** Backup Alarm

VT210 TRACK LOADER

SPECIFICATIONS

| | | IMPERIAL | METRIC |
|---------------------|---|----------------------|------------|
| WEIGHT + DIMENSIONS | Operating Weight | 8865 lbs | 4021 kg |
| | Overall Operating Height - Fully Raised | 158.5" | 4026 mm |
| | Height to Hinge Pin - Fully Raised | 121" | 3073 mm |
| | Overall Height to Top of ROPS | 80.5" | 2045 mm |
| | Dump Angle at Full Height | 42° | |
| | Dump Height - Fully Raised | 90.5" | 2300 mm |
| | Rollback Angle Fully Raised | 92° | |
| | Overall Length with Bucket | 139.5" | 3543 mm |
| | Dump Reach at Full Height | 36.5" | 927 mm |
| | Rollback Angle at Ground | 29° | |
| | Seat to Ground Height | 38" | 965 mm |
| | Crawler Base | 54.5" | 1384 mm |
| | Overall Width - Less Bucket | 65.9" | 1674 mm |
| | Ground Clearance to Chassis | 7.5" | 191 mm |
| | Overall Length without Bucket | 108" | 2743 mm |
| | Specified Height | 86.5" | 2197 mm |
| | Reach at Specified Height | 38.5" | 978 mm |
| | Departure Angle | 30° | |
| | Clearance Radius - Front with Bucket | 87" | 2210 mm |
| | Clearance Radius - Front without Bucket | 54" | 1374 mm |
| CAPACITIES | Operating Capacity at 35% Tipping Load | 2100 lbs | 952 kg |
| | Operating Capacity at 35% Tipping Load with Side Weights | 2200 lbs | 998 kg |
| | Operating Capacity at 50% Tipping Load | 3000 lbs | 1361 kg |
| | Operating Capacity at 50% Tipping Load with Optional Side Weights | 3150 lbs | 1429 kg |
| ENGINE | Make / Model | Yanmar / 4TNV98C-NGL | |
| | Type | Stage 5 | |
| | Gross Power | 69.3 HP | 51.7 kW |
| | Net Power | 68.4 hp | 51 kW |
| | Maximum Torque @ 1625 rpm | 178 ft/lbs | 241 Nm |
| | Battery | 12 V | 3.0 kW |
| PERFORMANCES | Travel Speed | 6.4 mph | 10.3 km/hr |
| | Travel Speed with 2-Speed Option | 9.5 mph | 15.3 km/hr |
| | Tractive Effort | 9141 lbs | 4146 kg |

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- **NEW** Battery Disconnect
- Brake Control (Auto/Manual)
- **NEW** Color Display with Keyless Start + Security Code
- **NEW** Dual Flange Idlers - Front + Rear
- **NEW** Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- High-Back Adjustable Seats
- IdealTrax™ Auto Tensioning System
- Flip-Up Cooler
- Foot Throttle / **NEW** Deceleration Pedal
- Hand Throttle
- Horn
- Hydraloc™ Safety System
- Hydraglide™ Ride Control
- **NEW** Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- **NEW** LED Tail + Work Lights
- **NEW** Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- 12-Volt + USB Charging Ports
- Two Speed Drive
- Sloped Roof
- Greasable Pins
- Manual Attach
- 4-Point Lift
- Sound Reduction Package

OPTIONAL FEATURES

- 14-Pin Attachment System
- Air Conditioning in Cab Enclosure
- Bluetooth Hands-Free Radio
- Cab Enclosure
- Cast Rear Bumper
- Side Counterweights
- **NEW** Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- **NEW** Impact Side Windows
- **NEW** LED Road Light Package
- **NEW** LED Side Lights
- FOPS Level II with Light Guard
- Rearview Camera
- Rearview Mirror
- **NEW** Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat - Air Ride or Mechanical
- **NEW** Cloth, Heated Seat with Air Suspension and Extended Backrest
- 4-Way Flashers
- Sliding Side Windows



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517