

VT230

TRACK LOADER



KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- IdealTrax™ Auto Tensioning System
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Dual Flange Idlers - Front + Rear
- **NOW STANDARD** Pilot Joystick Controls
- **NOW STANDARD** Backup Alarm

*Optional features

VT230 TRACK LOADER

SPECIFICATIONS

	IMPERIAL	METRIC
WEIGHT + DIMENSIONS	Operating Weight	9250 lbs / 4196 kg
	Overall Operating Height - Fully Raised	158.5" / 4026 mm
	Height to Hinge Pin - Fully Raised	121" / 3073 mm
	Overall Height to Top of ROPS	80.5" / 2045 mm
	Dump Angle at Full Height	42°
	Dump Height - Fully Raised	90.5" / 2300 mm
	Rollback Angle Fully Raised	92°
	Overall Length with Bucket	141.3" / 3589 mm
	Dump Reach at Full Height	36.5" / 927 mm
	Rollback Angle at Ground	29°
	Seat to Ground Height	38" / 965 mm
	Crawler Base	54.5" / 1384 mm
	Overall Width - Less Bucket	69" / 1753 mm
	Ground Clearance to Chassis	7.5" / 191 mm
	Overall Length without Bucket	109.8" / 2789 mm
	Specified Height	86.5" / 2197 mm
	Reach at Specified Height	38.5" / 978 mm
	Departure Angle	28°
	Clearance Radius - Front with Bucket	88" / 2235 mm
	Clearance Radius - Front without Bucket	54" / 1374 mm
CAPACITIES	Operating Capacity at 35% Tipping Load	2300 lbs / 1043 kg
	Operating Capacity at 35% Tipping Load with Side Weights	2400 lbs / 1089 kg
	Operating Capacity at 50% Tipping Load	3286 lbs / 1490 kg
	Operating Capacity at 50% Tipping Load with Optional Side Weights	3436 lbs / 1559 kg
ENGINE	Make / Model	Yanmar / 4TNV98CT-XNGL
	Type	Stage 5
	Gross Power	72 HP / 53.7 kW
	Net Power	70.7 HP / 52.7 kW
	Maximum Torque @ 1800 rpm	217 ft/lbs / 294 Nm
PERFORMANCES	Battery	12 V / 3.0 kW
	Travel Speed	6.4 mph / 10.3 km/hr
	Travel Speed with 2-Speed Option	9.5 mph / 15.3 km/hr
	Tractive Effort	9126 lbs / 4139 kg

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- **NEW** Battery Disconnect
- Brake Control (Auto/Manual)
- **NEW** Color Display with Keyless Start + Security Code
- **NEW** Dual Flange Idlers - Front + Rear
- **NEW** Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- High-Back Adjustable Seats
- IdealTrax™ Auto Tensioning System
- Flip-Up Cooler
- Foot Throttle / **NEW** Deceleration Pedal
- Hand Throttle
- Horn
- Hydraloc™ Safety System
- Hydraglide™ Ride Control
- **NEW** Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- **NEW** LED Tail + Work Lights
- **NEW** Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- 12-Volt + USB Charging Ports
- Two Speed Drive
- Sloped Roof
- Greasable Pins
- Manual Attach
- 4-Point Lift
- Sound Reduction Package

OPTIONAL FEATURES

- 14-Pin Attachment System
- Air Conditioning in Cab Enclosure
- Bluetooth Hands-Free Radio
- Cab Enclosure
- Cast Rear Bumper
- Side Counterweights
- **NEW** Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- **NEW** Impact Side Windows
- **NEW** LED Road Light Package
- **NEW** LED Side Lights
- FOPS Level II with Light Guard
- Rearview Camera
- Rearview Mirror
- **NEW** Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat - Air Ride or Mechanical
- **NEW** Cloth, Heated Seat with Air Suspension and Extended Backrest
- 4-Way Flashers
- Sliding Side Windows



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517