VT275 TRACK LOADER





KEY FEATURES

- NEW Color Display with Keyless Start + Security Code
- IdealTrax™ Auto Tensioning System
- NEW Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- NEW LED Work, LED Rear Lights + Egress Lighting

- Vertical Lift Arm for More Reach at Dump Height
- NOW STANDARD Hydraglide™ Ride Control
- NEW Dual Flange Idlers Front + Rear
- **NOW STANDARD** Pilot Joystick Controls
- NOW STANDARD Backup Alarm

*Optional features



VT275 TRACK LOADER

SPECIFICATIONS

10051 lbs 4559 kg Operating Weight Overall Operating Height - Fully Raised 167 9" 4265 mm Height to Hinge Pin - Fully Raised 129.5" 3289 mm Overall Height to Top of ROPS 82" 2082 mm Dump Angle at Full Height Dump Height - Fully Raised 98.5" 2502 mm Rollback Angle Fully Raised Overall Length with Bucket 150' 3810 mm Dump Reach at Full Height 34.6 879 mm Rollback Angle at Ground Seat to Ground Height 39.5 1003 mm Crawler Base 64 3" 1633 mm Overall Width - Less Bucket 71" 1803 mm Ground Clearance to Chassis Q" Overall Length without Bucket Specified Height 89" 2261 mm Reach at Specified Height 54.4" 1382 mm Departure Angle Clearance Radius - Front with Bucket 93" 2362 mm Clearance Radius - Front without Bucket 58.5 1486 mm Clearance Radius - Rear 69" 1753 mm Bucket Width 74" 1880 mm Standard Track Width 15.7" 400 mm Operating Capacity at 35% Tipping Load 2750 lbs 1247 kg Operating Capacity at 35% Tipping Load with Side Weights 2870 lbs 1302 kg Operating Capacity at 50% Tipping Load 3929 lbs 1782 kg Operating Capacity at 50% Tipping Load with Optional Side Weights 1860 kg 4100 lbs Make / Model Yanmar / 4TNV98CT-XNGL Туре Gross Power 72 HP 53.7 kW Net Power 70.7 HP 52.7 kW Maximum Torque @ 1800 rpm 217 ft/lbs 294 Nm 12 V 3.0 kW 8.9 km/hr Travel Speed 5.5 mph Travel Speed with 2-Speed Option 8.4 mph 13.5 km/hi

IMPERIAL

10789 lbs

4894 kg

METRIC

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- NEW Battery Disconnect
- Brake Control (Auto/Manual)
- NEW Color Display with Keyless Start + Security Code
- NEW Dual Flange Idlers Front + Rear
- NEW Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- High-Back Adjustable Seats
- IdealTrax™ Auto Tensioning System
- Flip-Up Cooler
- Foot Throttle / NEW Deceleration Pedal
- Hand Throttle
- Horn
- Hydraloc™ Safety System
- Hydraglide™ Ride Control
- NEW Hydraulic Variable Speed Fan
- Hydrostatic Drive Servo
- Integral Access Plate (removable)
- NEW LED Tail + Work Lights
- NEW Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- 12-Volt + USB Charging Ports
- Two Speed Drive
- Sloped Roof
- Greasable Pins
- Manual Attach
- 4-Point Lift
- Sound Reduction Package

OPTIONAL FEATURES

- 14-Pin Attachment System
- Air Conditioning in Cab Enclosure
- Bluetooth Hands-Free Radio
- Cab Enclosure
- · Cast Rear Bumper
- Side Counterweights
- NEW Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- NEW Impact Side Windows
- NEW LED Road Light Package
- NEW LED Side Lights
- FOPS Level II with Light Guard
- Rearview Camera
- Rearview Mirror
- NEW Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat Air Ride or Mechnical
- NEW Cloth, Heated Seat with Air Suspension and Extended Backrest
- 4-Way Flashers
- Sliding Side Windows



West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517

© 2023 Manitou Equipment America, LLC. All registered and unregistered marks are owned by Manitou Equipment America, LLC or its affiliates. All rights reserved.

[®] denotes registration in the United States. Trademarks may or may not be registered in other countries.