

Technical sheet :


78 SEC S3




PHOTOS NON CONTRACTUELLES/NON-CONTRACTUAL PHOTOS

Capacities		Metric
Working height maximum (indoor)	h21	7.85 m
Working height maximum (outdoor)	h21	6.47 m
Platform height maximum (indoor)	h7	5.85 m
Platform height maximum (outdoor)	h7	4.47 m
Platform capacity	Q	227 kg
Lift capacity - Extension deck		113 kg
Number of people (inside / outside)		2 / 1
Weight and dimensions		
Platform weight*		1329 kg
Platform dimensions (length x width)	lp / ep	1.66 m x 0.76 m
Platform dimensions with extension (length)		2.55 m
Overall width	b1	0.82 m
Overall length	l1	1.83 m
Overall height	h17	2.16 m
Overall height (stowed)	h18	1.8 m
External turning radius	Wa3	1.55 m
Ground clearance	m4	0.08 m
Ground clearance with pothole guards deployed	m6	0.02 m
Wheelbase	y	1.32 m
Performances		
Drive speed - stowed		4 km/h
Drive speed - raised		0.8 km/h
Raise speed / Lower speed		26 s / 22 s
Gradeability		25 %
Permissible leveling (front / side)		3 ° / 1.5 °
Wheels		
Tyres type		Non marking
Dimensions of front wheels / rear wheels		0,305 x 0,115 - 0,305 x 0,115
Drive wheels (front / rear)		2 / 0
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		2 / 2
Engine/Battery		
Battery / Batteries capacity		24 V / 225 Ah
Integrated charger (V / Ah)		24 V / 27 Ah
Miscellaneous		
Ground Pressure		11.17 daN/cm²
Hydraulic tank capacity		14.20 l
Noise to environment (LwA)		< 70 dB(A)
Vibration on hands/arms		< 2.5 m/s²
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)

Load chart



Dimensional drawing



Equipment

Standard

2 flashing LED beacons

2 swing out component trays

220V predisposition in the platform

Anti-slip platform surface

Audible alarm and illuminated indicator lamp (leveling, overload, lowering)

Battery charge indicator lamp

CAN bus technology

Descent alarm

Dynamic hydraulic braking on front wheels

Emergency stop at ground controls

Folding rails with half height swing gate

Hom in the platform

Hour meter

Integrated diagnostic assistance

Load management according to environment (indoor/outdoor)

Manual emergency lowering

Monobloc semi-traction battery

Multi-voltage integrated charger

Non-marking rubber tyres

Pothole protection with automatic operation

Rear wheel multiple disc brakes

Side and rear forklift pockets

Optional

Air predisposition

Beep on every movement

Biodegradable oil

Extreme cold oil

Safety harness



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes