



TM

VENIERI
SPA

PRODUCT LINE

LOADERS
TELESCOPIC WHEEL LOADERS
BACKHOE TOOL CARRIERS





Venieri 70

1948-2018

Ferdinando and Carlo Venieri create the first **Venieri crawler tractor**



1948

Started co-operation with **Perkins** engine



1954

New fully-equipped plant opens



Production of **hydrostatic forklift** begins



1962

Venieri became **limited company (L.T.D.)** strengthening his name on the domestic market



1974

Production of **earthmoving machines** begins



Venieri introduces the **world's first hydrostatic transmission** in earthmoving machines



Introduction of a **new type of backhoe loader**



1986

Actual **new plants** open.



Production of the **rigid type** of Backhoe Loader has been **discontinued**



Venieri patented the world's **first electrical backhoe loader**



1999

100% Green Power Company



2002

Hydrostatic transmission started to be installed in **all machines**



75 Worldwide Partners



Venieri introduces **STAGE IV/TIER 4F**



2016

QUALITY MEETS HISTORY.



2018

WHEEL LOADERS



13.63C



10.63D

<i>Linkage</i>	"Z" BAR	PARALLEL
<i>Engine Max Power</i>	184 HP	143 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f	STAGE 5/TIER 4f
<i>Breakout Force</i>	12.000 Kg	8.000 Kg
<i>Static Tipping Load, Full Turn</i>	9.600 Kg	5.200 Kg
<i>Bucket Capacity, Min/Max</i>	2,7 - 3,0 m ³	1,8 - 2,2 m ³
<i>Max Permissible Weight</i>	14.150 Kg	10.110 Kg
<i>Tyres</i>	20,5 R25	17,5 x 25
<i>Forks Load Capacity (EN 474-3)</i>	5.600 Kg	3.400 Kg
<i>Max Speed</i>	40 Km/h	40 Km/h



5.63D



4.63H

<i>Linkage</i>	"Z" BAR	"Z" BAR
<i>Engine Max Power</i>	79 HP	72 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f	STAGE 5/TIER 4f
<i>Breakout Force</i>	6.400 Kg	5.600 Kg
<i>Static Tipping Load, Full Turn</i>	4.400 Kg	4.200 Kg
<i>Bucket Capacity, Min/Max</i>	1,1 - 1,5 m ³	1,0 - 1,5 m ³
<i>Max Permissible Weight</i>	6.270 Kg	6.200 Kg
<i>Tyres</i>	405/70 R20	16/70 x 20
<i>Forks Load Capacity (EN 474-3)</i>	2.720 Kg	2.560 Kg
<i>Max Speed</i>	40 Km/h	30 Km/h



9.63D

"Z" BAR
143 HP
STAGE 5/TIER 4f
8.600 Kg
5.500 Kg
1,8 - 2,2 m³
10.110 Kg
17,5 x 25
3.680 Kg
40 Km/h



8.63C HL

PARALLEL
128 HP
STAGE 5/TIER 4f
9.400 Kg
4.600 Kg
1,2 m³
8.750 Kg
460/70 R24
2.800 Kg
40 Km/h



2.63D Plus

"Z" BAR
53 HP
STAGE 5/TIER 4f
5.300 Kg
3.000 Kg
0,75 - 1,2 m³
4.800 Kg
12,0/75 x 18
1.920 Kg
28 Km/h



2.63D

"Z" BAR
53 HP
STAGE 5/TIER 4f
4.700 Kg
2.700 Kg
0,70 - 1,2 m³
4.800 Kg
12,0/75 x 18
1.760 Kg
20 Km/h



1.63D

"VZPK"
53 HP
STAGE 5/TIER 4f
3.840 Kg
1.850 Kg
0,5 - 0,8 m³
3.600 Kg
12 - 16,5
1.104 Kg
40 Km/h



7.63D

"Z" BAR
128 HP
STAGE 5/TIER 4f
9.100 Kg
5.000 Kg
1,4 - 2,0 m ³
8.750 Kg
15,5 x 25
3.000 Kg
40 Km/h



1.33C

PARALLEL
53 HP
STAGE 5/TIER 4f
2.300 Kg
2.000 Kg
0,45 m ³
4.130 Kg
12 - 16,5
1.200 Kg
20 Km/h



TELESCOPIC WHEEL LOADERS

8.63TL

<i>Linkage</i>	TELESCOPIC ARM
<i>Engine Max Power</i>	143 HP
<i>Engine Emission</i>	STAGE 4/TIER 4f
<i>Maximum Loading Height with Forks - Telescopic Extended</i>	5.280 mm
<i>Bucket Capacity, Min/Max</i>	1,2 m ³
<i>Max Permissible Weight</i>	9.100 Kg
<i>Tyres</i>	460/70 R24
<i>Forks Load Capacity (EN 474-3)</i>	3.200 Kg
<i>Max Speed</i>	40 Km/h



1.63B TL

<i>Linkage</i>	TELESCOPIC ARM
<i>Engine Max Power</i>	53 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f
<i>Maximum Loading Height with Forks - Telescopic Extended</i>	3.700 mm
<i>Bucket Capacity, Min/Max</i>	0,5 m ³
<i>Max Permissible Weight</i>	4.000 Kg
<i>Tyres</i>	31x15,50 - 15,3
<i>Forks Load Capacity (EN 474-3)</i>	1.250 Kg
<i>Max Speed</i>	40 Km/h

BACKHOE TOOL CARRIERS



8.23G



10.23E

<i>Linkage</i>	"Z" BAR	"Z" BAR
<i>Engine Max Power</i>	106 HP	106 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f	STAGE 5/TIER 4f
<i>Breakout Force</i>	6.900 Kg	10.800 Kg
<i>Static Tipping Load, Full Turn</i>	5.250 Kg	6.150 Kg
<i>Bucket Capacity, Min/Max</i>	1,1 - 1,4 m³	1,3 - 2,0 m³
<i>Max Permissible Weight</i>	8.490 Kg	9.920 Kg
<i>Tyres</i>	16/70 x 24	17,5L x 24
<i>Forks Load Capacity (EN474-3)</i>	3.120 Kg	3.880 Kg
<i>Max Speed</i>	40 Km/h	40 Km/h
<i>Max Digging Depth, Std./Telescopic</i>	4,6 - 5,4 m	5,0 - 6,0 m



1.33C

<i>Linkage</i>	PARALLEL
<i>Engine Max Power</i>	53 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f
<i>Breakout Force</i>	2.300 Kg
<i>Static Tipping Load, Full Turn</i>	2.000 Kg
<i>Bucket Capacity, Min/Max</i>	0,45 m³
<i>Max Permissible Weight</i>	4.130 Kg
<i>Tyres</i>	12 - 16,5
<i>Forks Load Capacity (EN474-3)</i>	1.200 Kg
<i>Max Speed</i>	20 Km/h
<i>Max Digging Depth, Std./Telescopic</i>	2,75 - 3,25 m



VENIERI SPA



The illustrations on the present folder do not necessarily show the product standard version. Data and dimensions described in this folder are not binding. Venieri reserves the right of carrying out possible changes at any time and without previous notice because of its policy of steady development and improvement of the products.



www.vf-venieri.com



Via Piratello, 106 - 48022 Lugo (RA) ITALY
Tel. +39 0545 904411 - Fax +39 0545 30389
e-mail: info@vf-venieri.com www.vf-venieri.com

Spare Parts

Tel. +39 0545 904429 Fax +39 0545 24555
e-mail: ricambi@vf-venieri.com