

GEHL

SKID LOADERS



GEHL
WORKS LIKE YOU™



**BORN ON AN
AMERICAN FARM
IN 1859.**

GEHL[®]

WORKS LIKE YOU[™]

Starting in 1859 GEHL has been rooted in agriculture. Designing and building machines to help America's hardest workers. Many years later, we are offering products world-wide that work just as hard as the people who own and operate them.

We build machines that make life easier and exceed expectations. Here at GEHL we know that true satisfaction isn't felt while earth-moving but looking back at a job well-done. That is the true payoff for our operators and built in our DNA at GEHL.

For over 160 years we have been partnering with farmers, construction crews, landscapers and rental companies – large and small – to help move mountains and build a strong foundation of trust. **We care about our operators.** Safety and efficiency go into every machine we produce to help hardworking people get home safe and maybe even a little bit early. ■

The true payoff comes in a job well-done.



GEHL

**RAISED ON
A GLOBAL
JOB SITE.**

We have always designed and built machines to help the needs of the people who change our landscape. Over time, regulations and the needs of these workers change. GEHL continues to innovate and change with them to supply the most robust durable machines on the market.

Humble and hard working people, responsible for molding and changing the world around us are not overlooked by our brand. With that in mind, GEHL has contributed heavily to the construction industry and is dedicated to continue for many years to come.

GEHL has invested significantly into the future of our products and will continue to change and meet the requirements of urban job sites. Driven by the voice of our customers and industry data we are committed to be here to design, build, service and stand behind our products. We will help you do the heavy lifting.

As the global landscape changes we stay on track supplying machines that are reliable and meet or exceed emissions standards for the future of our planet and our young operators of tomorrow. ■

SKID LOADERS



R105

Height to Hinge Pin-Fully Raised
- 2731 mm
Rated Operating Capacity
- 476 kg
Operating Weight
- 1905 kg

RADIAL LIFT

Ultra Compact
H - 1.8 m / W - 1.2 m / L - 2.3 m
Perfect Rental Machine
Easy to Transport



R135

Height to Hinge Pin-Fully Raised
- 2794 mm
Rated Operating Capacity
- 612 kg
Operating Weight
- 2384 kg

RADIAL LIFT

Compact
H - 1.9 m / W - 1.4 m / L - 2.3 m
Pilot Joystick Controls
Great for Rental
Easy to Transport



R165

Height to Hinge Pin-Fully Raised
- 3018 mm
Rated Operating Capacity
- 748 kg
Operating Weight
- 2796 kg

RADIAL LIFT

Compact
H - 2 m / W - 1.6 m / L - 2.4 m
Optional Pilot Joystick Controls
Wicked Speed
Operator Favorite



R190^{GEN-2}

Height to Hinge Pin-Fully Raised
- 3023 mm
Rated Operating Capacity
- 862 kg
Operating Weight
- 3173 kg

RADIAL LIFT

Compact
H - 1.9 m / W - 1.6 m / L - 2.4 m
Largest Radial Lift Loader
Powerful Lifting
Operator Must-Have



V210

Height to Hinge Pin-Fully Raised
- 3073 mm
Rated Operating Capacity at 50%
- 952 kg
Operating Weight
- 3393 kg

VERTICAL LIFT

Mid-Size Loader
H - 2 m / W - 1.6 m / L - 3.5 m
Pilot Joystick Controls
Expanded Lift Height



V230

Height to Hinge Pin-Fully Raised
- 3099 mm
Rated Operating Capacity at 50%
- 1043 kg
Operating Weight
- 3515 kg

VERTICAL LIFT

Mid-Size Loader
H - 2.1 m / W - 1.7 m / L - 3.6 m
Great for Construction
Manufacturer's Favorite



V275

Height to Hinge Pin-Fully Raised
- 3277 mm
Rated Operating Capacity
- 1247 kg
Operating Weight
- 3719 kg

VERTICAL LIFT

Mid-Size Loader
H - 2.1 m / W - 1.7 m / L - 3.8 m
Joystick Controls Standard
Powerful Design



NEW! V325

Height to Hinge Pin-Fully Raised
- 3409 mm
Rated Operating Capacity
- 1474 kg
Operating Weight
- 4128 kg

VERTICAL LIFT

Large Loader
H - 2.1 m / W - 1.9 m / L - 3.9 m
Load Sensing Hydraulics
Yanmar Engine



NEW! V335

Height to Hinge Pin-Fully Raised
- 3409 mm
Rated Operating Capacity
- 1520 kg
Operating Weight
- 4461 kg

VERTICAL LIFT

Large Loader
H - 2.1 m / W - 1.9 m / L - 3.9 m
Deutz Engine
Load Sensing Hydraulics



NEW! V360

Height to Hinge Pin-Fully Raised
- 3454 mm
Rated Operating Capacity
- 1633 kg
Operating Weight
- 4681 kg

VERTICAL LIFT

Large Loader
H - 2.1 m / W - 1.9 m / L - 4 m
Load Sensing Hydraulics
Highest Dumping Height

KEEPING YOU ROLLIN'

VISIBILITY

Excellent sightlines from all sides for safe and precise placement of loads and reduced jobsite incidents. A high-mounted seat provides an excellent vantage point to the attachment and cutting-edge.

NEW! SLOPED ROOF

Our newly designed roof minimizes the front, upper cross section to improve your visibility. With the roof pitched in the middle, it directs rainfall and other debris to your outer edges, keeping your eyes on the attachment and job at hand.

Available on V210, V230, V275, V325, V335 and V360 only

CLIMATE CONTROL

Upgrade to Pressurized Cab Enclosure with air conditioning and heat to utilize the most of your machine. No matter the weather, you'll be running comfortably. Optional air ride seat and Bluetooth radio are two additions that help any operator with long hours of operation.

SAFETY

Our heavy duty doors offer operator protection, easy entry/exit and are well sealed for maximum operator climate controlled comfort. Add AC/Heat and you'll feel the difference and never go back.

NEW! SLOPED LIFT ARMS

New design to give a better view to your surroundings. It also limits the material build up on top of arms, while keeping your hydraulic lines protected.

Available on V210, V230, V275, V325, V335 and V360 only

MAINTENANCE

Excellent service access and quality components pair up to provide durable machines that are easy to maintain.

IdealAccess® - INDUSTRY EXCLUSIVE

A proprietary feature of the Pilot Series skid loaders is the IdealAccess® fold-up door. The optional fold-up door design provides an overall machine operating height that is several inches lower than machines with over-head door systems. It's unique in the fact that it folds up and everything stays in front of the operator, providing more overhead room free of obstructions. Available on V210, V230, V275, V325, V335 and V360

NEW! HYDRAULIC LOAD SENSING

Improve your efficiency with our new hydraulic load sensing. Reduce fuel consumption and boosts performance by powering the functions at correct levels.

Available on V325, V335 and V360 only

REAR BUMPER

The rear bumper protects the rear of the machine from accidental damage and increases the rated operating capacity.*

**Increases capacity on V210, V325 and V335*

SERVICE

Easy access to the chain case makes maintenance and repairs much faster getting you back on the job site or in the fields with minimal down time to your machine. Greasable pins make daily maintenance a breeze.*

**V210, V230, V275, V325, V335 and V360 only*

ATTACHMENTS

A full line of attachments and accessories are designed specifically to fill operators' needs, making their GEHL the most versatile machine on the job site. Some popular attachments that transform your machines in minutes are: Augers, Backhoes, Bale Clamps/Spears, Brooms, Mowers, High Dump Buckets, Grapples, and Pallet Forks. Upgrade to hydraulic Power-A-Tach® to change and secure new attachments without leaving the comfort of your cab.

NEW MODELS

V325 | V335 | V360

• 23% More Cab Volume

• Over 20% Increased Visibility

• Easy Entrance Lowered 3"

• Increased Ground Speeds

• Re-Imagined Serviceability

LET'S GET INSIDE

WE UNDERSTAND THE CAB IS YOUR OFFICE.

We offer many standard and optional features to improve operator comfort and know the importance of being comfortable while working. Not only for operator fatigue but also for overall job site safety and employee retention. A comfortable and alert operator is a safe operator. Please consider these well-thought-out features and the benefits your crew will have when building your next loader.

PRESSURIZED CAB

An optional pressurized, sealed cab enclosure provides a cleaner, quieter operating environment.

INTERIOR LIGHTS

We know our operators start at dawn and work past dusk, so we have interior lights and optional additional work lights to fit your needs.

EXCELLENT VIEWS FROM ALL SIDES

Safe, clear visibility for precise operation. Rear window is removable for alternative exit in emergencies.

OVER 20% INCREASED VISIBILITY on V210, V230, V275, V325, V335 + V360

POWER PORT

12-volt accessory plug keeps your devices fully charged. USB Port also available on V210, V230, V275, V325, V335 + V360.



2" (51 MM) SEATBELT

Optional 3" (76 mm) seatbelt available.

CONTROL OPTIONS

Hand/Foot, T-Bar, Dual-hand or Joystick available on selected models.*
*Not available on all models



DUAL-HAND



T-BAR



HAND/FOOT



JOYSTICK

ADJUSTABLE CONTROLS

Controls extend and retract to provide personalized comfort.

SPACIOUS COMFORT

Keeping you comfortable after a long day and some models have easy removable foot plate or easy cleaning of the cabin floor.

23% LARGER CABS on V210, V230, V275, V325, V335 + V360



BEST IN CLASS - STANDARD ROPS II OVERHEAD PROTECTION

Standard on R105, R135, R165, R190, V335 and V360
Optional on V210, V230, V275, V325, V335 and V360.

MULTIPLE AIR VENTS

Adjustable vents throughout the cab provide optimal temperature control.

HEAVY-DUTY SIDE PROTECTION

Sliding windows open for venting and communicating while still protected by single piece metal guarding.

EASY ENTRY AND EXIT

Large entry area allows for easy access to the operator station.

BLUETOOTH MP3 RADIO

Optional upgrade to wirelessly play music or podcasts using the speakers in the cab.

ADJUSTABLE SEAT

Choose between an air-ride suspension or mechanical suspension seat.

NEW BRANDED, HEATED, CLOTH SEAT available on V210, V230, V275, V325, V335 + V360

PADDED, ADJUSTABLE ARMRESTS

OPERATOR SAFETY

The machine safety system (Hydraloc™) allows operation only when the user is on the seat and the restraint bar is lowered into position.

CUP HOLDER

CLIMATE CONTROL

Heat is standard on all cab models. Air conditioning is an option on select models.

STORAGE COMPARTMENTS

Designed for your phone, keys and other items you need within arms reach.

VISIBILITY + SAFETY

Every machine we manufacture is inspired by safety—from a more comfortable cab that reduces operator fatigue to a pressure-sensitive seat that only works when a user sits with the restraint bar lowered. Clear visibility from all sides of the machine allow for precision operation that raises productivity and minimizes accidents. We also designed our Skid Loaders with heavy-duty

doors and the highest level of safety protection for an operator in a roll over or falling object situation with industry leading Level II Falling Object Protective Structure (FOPS) and Roll-Over Protective Structure (ROPS)*. At the end of the day, nothing is more important than ensuring you get home safe after leaving the jobsite.

**Optional Feature on R135, R165, V210, V230 and V275*

VERTICAL OR RADIAL?

Depending on your needs and situation, we offer both radial lift and vertical lift Skid Loaders. Our radial lift loaders offer extended reach at the middle of the lift path and are designed for easier, more accessible on-site serviceability. Our

vertical lift loaders provide more reach at full lift height, making them optimal for applications that require loading and stacking at high heights. Plus, you can increase the lift capacity of a vertical lift loader by keeping the load closer to the machine.

ADDITIONAL FEATURES ON OUR V210, V230, V275, V325 V335 +V360 MODELS

REAR VIEW CAMERA



This optional feature improves visibility and increases the safety of those around you while operating.

LARGER CABS

Cabin space has been increased by 23% allowing you to be even more comfortable all day long.

NEW DIGITAL DISPLAY




Check fuel consumption, engine RPM's, machine hours, engine diagnostic codes, warning indicators and much more. Additionally, you can now start your engine with keyless entry.

EASY ENTRANCE

The entrance of our cabs have been lowered 3", allowing you more space for efficient entry and exit.

KEEP YOUR PROJECT ROLLING

Skid loaders are usually the first of the machines to show up at a new build. The perfect machine for earthmoving, land prep and concrete flatwork. Get behind the controls of a GEHL skid loader at your local dealer and you'll feel the difference.



Scan with your phone to find your local dealer.

www.gehl.com/en-US/store-locator

SMALL FRAME SKID LOADERS



R105

Capacities	
Rated Operating Capacity	476 kg
Rated Operating Capacity w/Counterweight	533 kg
Unladen weight	1678 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	3607 mm
Height to Hinge Pin – Fully Raised	2731 mm
Overall Height to Top of ROPS	1784 mm
Dump angle at full height	40 °
Dump height	2083 mm
Overall length with bucket	2997 mm
Dump reach - Full height	641 mm
Rollback at ground	31 °
Seat to ground height	826 mm
Wheelbase	876 mm
Overall width less bucket	1224 mm
Bucket Width	1372 mm
Ground clearance	159 mm
Overall length - Less Bucket	2248 mm
Clearance Radius - Front with Bucket	1829 mm
Clearance Circle - Front without Bucket	1067 mm
Clearance Circle - Rear	1372 mm
Performances	
Travel speed (unladen)	8.26 km/h
Wheels	
Standard tires	27x8.5x15 HD
Engine	
Engine brand	Yanmar
Engine model	3TNV88C-BKMSR
Engine norm	Stage V
Gross Power (kW)	25.5 kW
Max. torque / Engine rotation	109 Nm / 1820 rpm
Battery	12 V
Starter (kW)	2.3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	55 l/min
Tank Capacities	
Fuel tank	37.9 l
Reservoir Capacity Hydraulics	30.30 l
Noise and Vibration	
Environmental noise (LwA)	101 dB
Whole-Body Vibration (ISO 2631-1)	1.12 m/s²
Vibration to whole hand/arm	< 1.70 m/s²



R135

Capacities	
Rated Operating Capacity	612 kg
Rated Operating Capacity w/ Counterweight	680 kg
Unladen weight	2161 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	3670 mm
Height to Hinge Pin – Fully Raised	2790 mm
Overall Height to Top of ROPS	1930 mm
Dump angle at full height	40 °
Dump height	2123 mm
Overall length with bucket	3073 mm
Dump reach - Full height	591 mm
Rollback at ground	28 °
Seat to ground height	871 mm
Wheelbase	950 mm
Overall width less bucket	1372 mm
Bucket Width	1372 mm
Ground clearance	201 mm
Overall length - Less Bucket	2360 mm
Clearance Radius - Front with Bucket	1842 mm
Clearance Circle - Front without Bucket	1120 mm
Clearance Circle - Rear	1372 mm
Performances	
Travel speed (unladen)	12.90 km/h
Wheels	
Standard tires	10.00x16.5 HD
Engine	
Engine brand	Yanmar
Engine model	4TNV88C
Engine norm	Stage V
Gross Power	34 kW
Max. torque / Engine rotation	146 Nm / 1820 rpm
Battery	12 V
Starter	2.3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	63.60 l/min
Tank Capacities	
Fuel tank	59.40 l
Reservoir Capacity Hydraulics	39.8 l
Noise and Vibration	
Environmental noise (LwA)	101 dB
Whole-Body Vibration (ISO 2631-1)	0.81 m/s²
Vibration to whole hand/arm	< 1.77 m/s²



R165

Capacities	
Rated Operating Capacity	748 kg
Rated Operating Capacity w/ Counterweight	816.50 kg
Unladen weight	2527 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	3876 mm
Height to Hinge Pin – Fully Raised	3018 mm
Overall Height to Top of ROPS	1956 mm
Dump angle at full height	38 °
Dump height	2380 mm
Overall length with bucket	3101 mm
Dump reach - Full height	579 mm
Rollback at ground	28 °
Seat to ground height	904 mm
Wheelbase	986 mm
Overall width less bucket	1580 mm
Bucket Width	1562 mm
Ground clearance	160 mm
Overall length - Less Bucket	2385 mm
Clearance Radius - Front with Bucket	1869 mm
Clearance Circle - Front without Bucket	1153 mm
Clearance Circle - Rear	1466 mm
Performances	
Travel Speed with Two-Speed - Maximum	19.50 km/h
Wheels	
Standard tires	10.00x16.5 HD
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NMS2V
Engine norm	Stage V
Gross Power (kW)	51.7 kw
Max. torque / Engine rotation	241 Nm / 1625 rpm
Battery	12 V
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	77 l/min
High-Flow Auxiliary Hydraulics – Option	114 l/min
Tank Capacities	
Fuel tank	62.50 l
Reservoir Capacity Hydraulics	39 l
Noise and Vibration	
Environmental noise (LwA)	101 dB
Whole-Body Vibration (ISO 2631-1)	1.05 m/s²
Vibration to whole hand/arm	< 1.53 m/s²



R190

Capacities	
Operating Capacity At 50% Tipping Load	862 kg
Operating Weight	3173 kg
Unladen Weight	2953 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	3993 mm
Height to Hinge Pin – Fully Raised	3023 mm
Overall Height to top of ROPS	1956 mm
Dump angle at full height	39 °
Dump height	2313 mm
Overall length with bucket	3261 mm
Dump reach - Full height	667 mm
Rollback at ground	28 °
Seat to ground height	904 mm
Wheelbase	1067 mm
Overall width less bucket	1575 mm
Bucket Width	1676 mm
Ground clearance	160 mm
Overall length - Less Bucket	2446 mm
Clearance Radius - Front with Bucket	2032 mm
Clearance Circle - Front without Bucket	1168 mm
Clearance Circle - Rear	1511 mm
Performances	
Travel Speed with Two-Speed - Maximum	19.47 km/h
Wheels	
Standard tires	10 x 16.5
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NMS2V
Engine norm	Stage V
Gross Power (kW)	51.7 kw
Max. torque / Engine rotation	241 Nm / 1625 rpm
Battery voltage	12 V
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	70.78 l/min
High-Flow Auxiliary Hydraulics	114 l/min
Tank Capacities	
Fuel tank	58.67 l
Reservoir Capacity Hydraulics	35.96 l
Noise and Vibration	
Environmental noise (LwA)	100 dB
Whole-Body Vibration (ISO 2631-1)	0.96 m/s²
Vibration to whole hand/arm	< 1.53 m/s²



MID + LARGE FRAME



V210

Capacities	
Operating Capacity At 50% Tipping Load	953 kg
Operating Weight	3393 kg
Unladen weight	3055 kg
Tipping capacity	1905 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	4054 mm
Height to Hinge Pin - Fully Raised	3061 mm
Overall Height to top of ROPS	2032 mm
Dump angle at full height	42 °
Dump height	2286 mm
Overall length with bucket	3543 mm
Dump reach - Full height	851 mm
Rollback Angle at Full Height	92 °
Seat to ground height	952.5 mm
Overall width less bucket	1623 mm
Ground clearance	178 mm
Overall length - Less Bucket	2743 mm
Clearance Radius - Front with Bucket	2146 mm
Clearance Circle - Rear	1664 mm
Performances	
Travel Speed with Two-Speed - Maximum	18.70 km/h
Travel speed (unladen)	12.10 km/h
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NGL
Engine norm	Stage V
Gross Power (kW)	51.7 kw
Max. torque / Engine rotation	241 Nm / 1625 rpm
Number of cylinders	4
Engine cooling system	Water
Battery voltage	12 V
Alternator - Ampere	100 A
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	86.50 l/min
Auxiliary Hydraulic Pressure	239.59 bar
High-Flow Auxiliary Hydraulics	114 l/min
High-Flow Auxiliary Hydraulics Pressure	229.25 bar
Tank Capacities	
Fuel tank	106 l
Reservoir Capacity Hydraulics	22.70 l

V230

Capacities	
Operating Capacity At 50% Tipping Load	1043 kg
Operating Weight	3515 kg
Unladen weight	3167 kg
Tipping capacity	2087 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	4079 mm
Height to Hinge Pin - Fully Raised	3099 mm
Overall Height to top of ROPS	2058 mm
Dump angle at full height	42 °
Dump height	2312 mm
Overall length with bucket	3589 mm
Dump reach - Full height	826 mm
Rollback Angle at Full Height	92 °
Seat to ground height	978 mm
Overall width less bucket	1707 mm
Ground clearance	203 mm
Overall length - Less Bucket	2789 mm
Clearance Radius - Front with Bucket	2171 mm
Clearance Circle - Rear	1689 mm
Performances	
Travel Speed with Two-Speed - Maximum	20 km/h
Travel speed (unladen)	12.70 km/h
Engine	
Engine brand	Yanmar
Engine model	4TNV98CT-XNGL
Engine norm	Stage V
Gross Power (kW)	53.7 kw
Max. torque / Engine rotation	294 Nm / 1800 rpm
Number of cylinders	4
Engine cooling system	Water
Battery voltage	12 V
Alternator - Ampere	100 A
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	86.50 l/min
Auxiliary Hydraulic Pressure	239.59 bar
High-Flow Auxiliary Hydraulics	114 l/min
High-Flow Auxiliary Hydraulics Pressure	229.25 bar
Tank Capacities	
Fuel tank	106 l
Hydraulic Tank Capacity	22.7 l

V275

Capacities	
Operating Capacity At 50% Tipping Load	1247 kg
Operating Weight	3719 kg
Unladen weight	3371 kg
Tipping capacity	2495 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	4252 mm
Height to Hinge Pin - Fully Raised	3277 mm
Overall Height to top of ROPS	2058 mm
Dump angle at full height	42 °
Dump height	2489 mm
Overall length with bucket	3810 mm
Dump reach - Full Height	830 mm
Rollback Angle at Full Height	92 °
Seat to ground height	978 mm
Overall width less bucket	1712 mm
Ground clearance	209 mm
Overall length - Less Bucket	3023 mm
Clearance Radius - Front with Bucket	2289 mm
Clearance Circle - Rear	1829 mm
Performances	
Travel Speed with Two-Speed - Maximum	17.50 km/h
Travel speed (unladen)	11.40 km/h
Engine	
Engine brand	Yanmar
Engine model	4TNV98CT-XNGL
Engine norm	Stage V
Gross Power (kW)	53.7 kw
Max. torque / Engine rotation	294 Nm / 1800 rpm
Number of cylinders	4
Engine cooling system	Water
Battery voltage	12 V
Alternator - Ampere	100 A
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	98.40 l/min
Auxiliary Hydraulic Pressure	239.59 bar
High-Flow Auxiliary Hydraulics	126 l/min
High-Flow Auxiliary Hydraulics Pressure	229.25 bar
Tank Capacities	
Fuel tank	106 l
Reservoir Capacity Hydraulics	22.70 l



V325

Capacities	
Operating Capacity at 50% Tipping Load	1474 kg
Rated Operating Capacity w/ Counterweight	1565 kg
Operating Weight	4128 kg
Tipping Capacity	2948 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	4389 mm
Height to Hinge Pin - Fully Raised	3409 mm
Overall Height to top of ROPS	2084 mm
Dump Angle at Full Height	41°
Dump Height	2634 mm
Overall Length with Bucket	3922 mm
Dump Reach - Full Height	846 mm
Rollback Angle at Full Height	94°
Seat to Ground Height	1039 mm
Overall Width Less Bucket	1852 mm
Ground Clearance	209 mm
Overall Length - Less Bucket	3124 mm
Clearance Radius - Front with Bucket	2299 mm
Clearance Circle - Rear	1905 mm
Performances	
Travel Speed with Two-Speed - Maximum	10.7 km/h
Travel speed (unladen)	17.3 km/h
Wheels	
Standard tires	12 x 16.5
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NGL
Gross Power	53.7 kw
Max. Torque / Engine Rotation	294 Nm / 1800 rpm
Starter	3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	94.6 l/min
Auxiliary Hydraulic Pressure	238 bar
High-Flow - Auxiliary hydraulics	129 l/min
High-Flow Auxiliary Hydraulics Pressure	229 bar
Tank Capacities	
Fuel tank	106 l
Hydraulic Tank Capacity	27 l



V335

Capacities	
Operating Capacity at 50% Tipping Load	1520 kg
Rated Operating Capacity w/ Counterweight	1610 kg
Operating Weight	4461 kg
Tipping Capacity	3040 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	4389 mm
Height to Hinge Pin - Fully Raised	3409 mm
Overall Height to top of ROPS	2084 mm
Dump Angle at Full Height	41°
Dump Height	2634 mm
Overall Length with Bucket	3922 mm
Dump Reach - Full Height	846 mm
Rollback Angle at Full Height	94°
Seat to Ground Height	1039 mm
Overall Width Less Bucket	1852 mm
Ground Clearance	209 mm
Overall Length - Less Bucket	3124 mm
Clearance Radius - Front with Bucket	2299 mm
Clearance Circle Rear	1905 mm
Performances	
Travel Speed with Two-Speed - Maximum	10.7 km/h
Travel speed (unladen)	19.5 km/h
Wheels	
Standard tires	12 x 16.5
Engine	
Engine brand	Deutz
Engine model	TCD3.6
Gross Power	74.4 kw
Max. Torque / Engine Rotation	410 Nm / 1600 rpm
Starter	4 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	95 l/min
Auxiliary Hydraulic Pressure	238 bar
High-Flow - Auxiliary hydraulics	151 l/min
High-Flow Auxiliary Hydraulics Pressure	238 bar
Tank Capacities	
Fuel tank	106 l
Hydraulic Tank Capacity	27 l



V360

Capacities	
Operating Capacity at 50% Tipping Load	1633 kg
Rated Operating Capacity w/ Counterweight	1724 kg
Operating Weight	4681 kg
Tipping Capacity	266 kg
Weight and Dimensions	
Overall Operating Height - Fully Raised	4435 mm
Height to Hinge Pin - Fully Raised	3454 mm
Overall Height to top of ROPS	2134 mm
Dump Angle at Full Height	41°
Dump Height	2678 mm
Overall Length with Bucket	3968 mm
Dump Reach - Full Height	798 mm
Rollback Angle at Full Height	94°
Seat to Ground Height	1085 mm
Overall Width Less Bucket	1916 mm
Ground Clearance	254 mm
Overall Length - Less Bucket	3173 mm
Clearance Radius - Front with Bucket	2350 mm
Clearance Circle - Rear	1943 mm
Performances	
Travel Speed with Two-Speed - Maximum	11.7 km/h
Travel speed (unladen)	20 km/h
Wheels	
Standard tires	14 x 17.5 HD
Engine	
Engine brand	Deutz
Engine model	TCD3.6
Gross Power	85 kw
Max. Torque / Engine Rotation	460 Nm / 1600 rpm
Starter	4 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	95 l/min
Auxiliary Hydraulic Pressure	238 bar
High-Flow - Auxiliary hydraulics	151 l/min
High-Flow Auxiliary Hydraulics Pressure	238 bar
Tank Capacities	
Fuel tank	106 l
Hydraulic Tank Capacity	27 l

MAXIMIZE YOUR MACHINE



Scan with your phone to learn more and see a video overview.

EQUIPMENT TRACKING

Geolocation, geofencing, hours of use, etc. You are in charge of defining when and where your machine can be operated. If it is stolen or used without authorization, you are notified immediately. Location, alerts, fuel consumption at your fingertips. Knowing your machine better, you can optimize how it is used and driven, improving financial and logistics management. Save time and enjoy a greater peace of mind. See the myGEHL App section below.

PREDICTIVE ANALYTICS

By accessing machine data, our technicians can anticipate routine maintenance operations and repairs with the needed parts, meaning issues are resolved quicker. By anticipating the maintenance operations that need to be performed, ensuring your machine is serviced at the most suitable time. The risk of unexpected breakdowns and downtime are substantially reduced.

A TRUE PARTNER

With the network of GEHL partners by your side, you can work in complete confidence and count on high-level support and practical help at any moment. Monitoring of machine events enables you to implement corrective actions and optimize your up-time while also helping you understand your total cost of ownership. If the machine is sold, you can also pass on its "ID card" to the new owner as a gesture of transparency.

STAY CONNECTED NO MATTER WHERE YOU ARE



The myGEHL app allows for simpler day-to-day operations. Get machine information such as location, fuel and DEF levels, consumption data and more. Access documentation and videos for more information about your machine in real time. All at the tip of your fingers.



FULL SUPPORT

With over 160 years of experience in the field of handling equipment, our priority at GEHL is to keep your machine operating at maximum productivity. It's a mission realized through constantly refined services and innovations. Precision engineered spare parts. Qualified technicians, certified at our state-of-the-art training center. And advances like real-time equipment monitoring, at your fingertips. Maximize uptime and longevity with genuine Manitou Group parts, maintain productivity and enhance security with real-time monitoring and access control and enjoy ultimate peace of mind with extended protection coverage.

MANITOU GROUP | ATTACHMENTS

MANITOU GROUP | PARTS

MANITOU GROUP | FINANCE

ALL NEW GEHL.COM



CHEK OUT THE NEW **GEHL.COM**

- SHOP MACHINES
- COMPARE MODELS
- FIND A DEALER
- LOCATE SUPPORT
- WORKING PHOTOS/VIDEOS

Also linked to our social media pages allowing you to join the conversation with other GEHL machine enthusiasts.



FROM YOUR COMPUTER
OR YOUR PHONE!

GEHL[®]

WORKS LIKE YOU[™]

[GEHL.COM](https://www.gehl.com)



Manitou Equipment America, LLC

P.O. Box 179

One GEHL Way

West Bend, WI, USA 53095

P: (262) 334-9461

F: (262) 338-7517

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

© 2026 Manitou Equipment America, LLC. All registered and unregistered marks are owned by Manitou Equipment America, LLC or its affiliates. All rights reserved.

® denotes registration in the United States. Trademarks may or may not be registered in other countries.